

**Sentry 2402W2** is a powerful battery monitoring system for Telecom -48V system with 2V cells up to 3,000Ah capacity. This compact battery unit combines superior data quality and flexible installation to address most cell site, central office and substation applications for effective remote battery management according to the IEEE updated standards:

**IEEE Std. 1188 - 2005: Recommended Practice for Maintenance, Testing, and Replacement of Valve-Regulated Lead- Acid (VRLA) Batteries for Stationary Applications ([IEEE Link](#))**

**IEEE Std. 450 - 2010: Recommended Practice for Maintenance, Testing, and Replacement of Vented Lead-Acid Batteries for Stationary Applications ([IEEE Link](#))**



### Front Panel

- Current Sensor
- Ambient Temperature
- Pilot Temperature
- RS232 and RS485
- Service Alarm
- Urgent Alarm
- Digital Input

### Rear Panel

- 2-wire mode
- Cell Voltage
- Internal Resistance
- Connection Resistance for each cell




### Main Features

- Super precise IR (Internal Resistance) measurement for each cell
- Discriminate inter-cell resistance measurement
- 16-bit high resolution data acquisition
- No mechanical relays, resulting high reliability for telecom applications
- Industry standard Modbus/RTU communication for high reliability and quick integration
- Compact design allows for easy installation on the top or inside of the battery cabinet.
- Industrial grade reliable connections
- Plug and play HMI panel (optional)
- Full support to networking battery management system
- Compatible with MyBattery Platform™ for web based remote monitoring.
- Ambient and Pilot Battery Temperature Monitoring

7309 York Road  
Towson, MD 21204  
United States

TEL +1 410-337-5233  
FAX +1 484-687-9904  
info@batterydaq.com  
www.batterydaq.com



## Specifications

<b>Power Supply</b>	
Power Input	Internal DC/DC converter, 36-60V input; Maximum Consumption: 10W
Isolation	500VDC@1min to battery string
<b>Current/Temperature Measurement</b>	
Current Sensor (Optional)	Support LEM HAS current sensor with internal +/-12V power supply (Default range +/- 400A, window size 20mmx10mm)
Accuracy	0.1% + sensor accuracy
Integrated Current Measurement	0.1A resolution (Field calibration is required.)
Temperature Sensors	1 ambient temperature sensor, 1 pilot temperature sensor
Range	Measurement range: -40 to 65°C
Accuracy	1 °C
<b>Voltage Measurement</b>	
Battery	24 x2V cell, up to 3,000Ah
Bus Voltage	Range: 36 – 60V; Accuracy: 0.1%
Input Range to Each Channel	+/- 3V for 2V batteries
Accuracy	0.1%
Input Wiring	2-wire differential input for each battery
<b>Internal Resistance</b>	
Range and Resolution	0 to 3mΩ, 0.001 mΩ resolution
2-wire mode	Internal Resistance and discriminate Connection Resistance.
<b>Communication</b>	
Serial Port	Isolated RS-232C and RS-485 interface
Protocol and Serial Settings	MODBUS RTU, 9600-8-1-None
Modbus address	1 to 28, configurable with HMI
Ethernet	Onboard Ethernet DTU to MyBattery Platform™
<b>Indication and Alarm</b>	
LED indication	<ul style="list-style-type: none"> <li>▪ Dual-color LEDs for status</li> <li>▪ Orange LED for service alarm</li> <li>▪ Red LED for urgent alarm</li> </ul>
Alarm Outputs	Service Alarm (Normal Close, 0.1A capacity) Urgent Alarm (Normal Close, 0.1A capacity)

**\*Specifications subject to change without notice**

7309 York Road  
 Towson, MD 21204  
 United States

TEL +1 410-337-5233  
 FAX +1 484-687-9904  
 info@batterydaq.com  
 www.batterydaq.com

